NSN 5962-01-093-2705

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-093-2705 **Body Length:** 0.785 inches **Body Width:** Between 0.240 inches and 0.295 inches **Body Height:** Between 0.160 inches and 0.180 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and low power and 3-state output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Design Function And Quantity:** 1 selector, data **Case Outline Source And Designator:** Mo-001-ag joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.5 volts power source **Time Rating Per Chacteristic:** 750.00 nanoseconds propagation delay time, low to high level output and 750.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-093-2705

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0