## NSN 5962-01-093-6162

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-093-6162 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** Between 0.245 inches and 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/storage and w/enable and w/clear and asynchronous and w/disable and expandable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 latch, addressable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 28.00 nanoseconds propagation delay time, low to high level output and 28.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0