NSN 5962-01-093-8805

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-093-8805

| Body Length: |
|--|
| 1.000 inches |
| Body Width: |
| 1.000 inches |
| Body Height: |
| 0.310 inches |
| Maximum Power Dissipation Rating: |
| 1050.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+100.0 degrees celsius |
| Features Provided: |
| Hybrid and negative outputs and positive outputs |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 2 input |
| |
| Design Function And Quantity: |
| Design Function And Quantity: 1 amplifier, operational, general purpose |
| |
| 1 amplifier, operational, general purpose |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit Shelf Life: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit Shelf Life: N/a |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit Shelf Life: N/a |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit Shelf Life: N/a Unit Of Measure: |
| 1 amplifier, operational, general purpose Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 15.0 volts power source Precious Material And Location: Terminal surface gold Precious Material: Gold Terminal Type And Quantity: 15 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: |