NSN 5962-01-093-8806

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-093-8806 **Body Length:** Between 0.370 inches and 0.400 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.135 inches and 0.145 inches **Maximum Power Dissipation Rating:** 170.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and low power and internally compensated and negative outputs and positive outputs **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic:

18.0 volts power source

Time Rating Per Chacteristic:

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

Yes - demil/mli

Fiig:

A458a0