

View Online at <https://aerobasegroup.com/nsn/5962-01-093-9931>

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

0.200 inches

Maximum Power Dissipation Rating:

77.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

E-3a

Features Provided:

Bipolar and schottky and burn in and monolithic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Triple 3 input

Design Function And Quantity:

3 gate

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

42.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Triple 3-input positive and gate

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

14.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0