## NSN 5962-01-094-5880



Memory Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-094-5880 **Body Length:** 0.870 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and bipolar and schottky and programmable and 3-state output and w/decoded output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 20418-es5499 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Fiig: A 45000

Demilitarization: Yes - demil/mli