NSN 5962-01-095-4264

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-095-4264 **Body Length:** 0.765 inches **Body Width:** 0.248 inches **Body Height:** 0.150 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and low power and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 4 switch, analog **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -5.0 volts power source and 20.0 volts power source **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Special Features:** Quad spst switch **Test Data Document:** 80063-sm-a-936074 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli