## NSN 5962-01-095-4885

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-095-4885

Overall Height:
Between 0.325 inches and 0.400 inches
Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and externally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Dual-in-line Control of the Control
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
D-1 mil-m-38510 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.0 volts input and 20.0 volts input
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 printed circuit
Specification Data:
81349-mil-m-38510/101 government specification
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

## NSN 5962-01-095-4885

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0