# NSN 5962-01-096-0291

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-096-0291

#### **Body Length:**

Between 0.660 inches and 0.785 inches

#### Body Width:

Between 0.220 inches and 0.280 inches

#### **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

750.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

#### Input Circuit Pattern:

2 input

## Case Outline Source And Designator:

T0-116 joint electron device engineering council

## **Terminal Surface Treatment:**

Tin

### Time Rating Per Chacteristic:

130.00 nanoseconds propagation delay time, low to high level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0