NSN 5962-01-096-2128

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-096-2128 **Body Length:** 0.896 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and negative outputs and high speed and low power and complementary outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 converter, digital to analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -18.0 volts power source and 18.0 volts power source **Time Rating Per Chacteristic:** 135.00 nanoseconds propagation delay time, low to high level output and 135.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Deminitarization

Yes - demil/mli

Fiig:

A458a0