NSN 5962-01-096-4121

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-096-4121 **Body Length:** 2.000 inches **Body Width:** 2.000 inches **Body Height:** 0.400 inches **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -25.0/+85.0 degrees celsius **End Application:** Cv-3399/byq **Features Provided:** Hermetically sealed and monolithic and high speed and negative outputs and positive outputs **Inclosure Material:** Metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -15.0 volts power source and 15.0 volts power source **Time Rating Per Chacteristic:** 900.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 23094-21071 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 34 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli