NSN 5962-01-096-6574

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-096-6574
Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.150 inches and 0.205 inches
Maximum Power Dissipation Rating:
200.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and asynchronous and synchronous and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
20 input
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
1200.00 nanoseconds propagation delay time, low to high level output and 1200.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
82577-932626 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli