NSN 5962-01-096-6575

Digital Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5962-01-096-6575 |
|--|
| Body Length: |
| Between 0.790 inches and 0.820 inches |
| Body Width: |
| 0.320 inches |
| Body Height: |
| Between 0.110 inches and 0.150 inches |
| Maximum Power Dissipation Rating: |
| 350.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and hybrid and high speed and w/open collector |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 2 channel |
| Design Function And Quantity: |
| 2 isolator, optical |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 82577-925439 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A458a0