

View Online at <https://aerobasegroup.com/nsn/5962-01-097-3887>

**Body Length:**

Between 0.740 inches and 0.830 inches

**Body Width:**

Between 0.275 inches and 0.310 inches

**Body Height:**

Between 0.080 inches and 0.150 inches

**Maximum Power Dissipation Rating:**

750.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and high speed and monolithic and positive outputs and w/switch and w/field effect transistor switch

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

Dual 3 input

**Design Function And Quantity:**

2 switch, analog

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

8.0 volts power source

**Time Rating Per Characteristic:**

300.00 nanoseconds propagation delay time, low to high level output and 260.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surface gold

**Precious Material:**

Gold

**Test Data Document:**

82577-932147 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0