

View Online at <https://aerobasegroup.com/nsn/5962-01-097-6785>

Body Length:

Between 0.750 inches and 0.780 inches

Body Width:

Between 0.245 inches and 0.275 inches

Body Height:

Between 0.140 inches and 0.160 inches

Maximum Power Dissipation Rating:

75.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-55.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and complementary outputs and negative outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

Triple 2 input

Design Function And Quantity:

3 receiver, line differential

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

0.0 volts power source

Time Rating Per Characteristic:

4.00 nanoseconds propagation delay time, low to high level output and 4.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0