

View Online at <https://aerobasegroup.com/nsn/5962-01-097-7469>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

600.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Aircraft, ac-130h, mc-130h, ec-130e, hc-130; aircraft bomber (atb); helicopter, cobra/tow, ah series; support equip, c-17a aircraft; strategic weapon systems (poseidon and trident); aircraft, phantom f-4; marine air traffic control landing systems; missile, minuteman lgm-30; nimitz class cvn; helicopter observation (ahip), oh-58d

**Features Provided:**

Hermetically sealed and hybrid and positive outputs

**Inclosure Material:**

Metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

1 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 reference, voltage, analog

**Case Outline Source And Designator:**

T0-39 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

40.0 volts power source

**Special Features:**

Weapon system essential

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0