NSN 5962-01-097-7472

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-097-7472

Body Outside Diameter: Between 0.335 inches and 0.370 inches Body Height: Between 0.155 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Foatures Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: B1349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: B1349-mil-m-38510/107a government specification Sheff Life: N/a Unit Of Measure:	
Body Height: Between 0.165 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-milh-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-milh-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Body Outside Diameter:
Between 0.165 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -56.0/+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mill-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mill-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Between 0.335 inches and 0.370 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Body Height:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Between 0.165 inches and 0.185 inches
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Operating Tempurature Range:
-65.0+150.0 degrees celsius Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solider Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	-55.0/+125.0 degrees celsius
Features Provided: Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Storage Tempurature Range:
Hermetically sealed and positive outputs and monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	-65.0/+150.0 degrees celsius
Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Features Provided:
Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Hermetically sealed and positive outputs and monolithic
Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Inclosure Material:
Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Metal
Input Circuit Pattern: 1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Inclosure Configuration:
1 input Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Can
Design Function And Quantity: 1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Input Circuit Pattern:
1 regulator, voltage Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	1 input
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Design Function And Quantity:
Solder Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	1 regulator, voltage
Voltage Rating And Type Per Characteristic: 35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Terminal Surface Treatment:
35.0 volts power source Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Solder
Test Data Document: 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Voltage Rating And Type Per Characteristic:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	35.0 volts power source
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Terminal Type And Quantity: 3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
3 pin Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data: 81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
81349-mil-m-38510/107a government specification Shelf Life: N/a Unit Of Measure:	3 pin
Shelf Life: N/a Unit Of Measure:	Specification Data:
N/a Unit Of Measure: 	81349-mil-m-38510/107a government specification
Unit Of Measure:	Shelf Life:
	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
Yes - demil/mli	Yes - demil/mli
Fiig:	Fiig:
A458a0	A458a0