NSN 5962-01-098-7636

Linear Microcircuit - Page 1 of 1

Demilitarization: Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-098-7636 **Body Length:** Between 0.740 inches and 0.830 inches **Body Width:** Between 0.275 inches and 0.310 inches **Body Height:** Between 0.050 inches and 0.180 inches **Maximum Power Dissipation Rating:** 900.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Burn in and hermetically sealed and high speed and compatible dtl and compatible rtl **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 1 input and dual 2 channel **Design Function And Quantity:** 2 driver, switch, field effect transistor **Terminal Surface Treatment:** Tin **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:**