NSN 5962-01-098-8881

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-098-8881

Body Outside Diameter: Between 0.335 inches and 0.370 inches Body Height: Between 0.165 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral	
Between 0.165 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	dy Outside Diameter:
Between 0.165 inches and 0.185 inches Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	tween 0.335 inches and 0.370 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	dy Height:
-55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	tween 0.165 inches and 0.185 inches
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	erating Tempurature Range:
Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	0.0/+125.0 degrees celsius
Features Provided: Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	orage Tempurature Range:
Hermetically sealed and monolithic and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	0.0/+150.0 degrees celsius
Inclosure Material: Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	atures Provided:
Glass and metal Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	rmetically sealed and monolithic and positive outputs
Inclosure Configuration: Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	losure Material:
Can Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	ass and metal
Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	losure Configuration:
Transistor-transistor logic Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	n
Input Circuit Pattern: Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	tput Logic Form:
Dual 2 input Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	insistor-transistor logic
Design Function And Quantity: 2 driver, peripheral Time Rating Per Chacteristic:	out Circuit Pattern:
2 driver, peripheral Time Rating Per Chacteristic:	al 2 input
Time Rating Per Chacteristic:	sign Function And Quantity:
	river, peripheral
55.00 paneseconds, propagation delay time. low to high level output and 40.00 paneseconds, propagation delay time, high to low low	ne Rating Per Chacteristic:
55.00 harroseconos propagation delay time, now to nigh level output and 40.00 harroseconos propagation delay time, high to low levi	00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output	put
Precious Material And Location:	ecious Material And Location:
Terminal surface gold	minal surface gold
Precious Material:	ecious Material:
Gold	ld .
Test Data Document:	st Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:	elf Life:
N/a	a de la companya de
Unit Of Measure:	it Of Measure:
Demilitarization:	militarization:
Yes - demil/mli	s - demil/mli
Fiig:	g:
A458a0	58a0