

View Online at <https://aerobasegroup.com/nsn/5962-01-099-6199>

**Body Length:**

0.960 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.130 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

794.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Features Provided:**

3-state output and w/enable and programmable and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Case Outline Source And Designator:**

D-6 mil-m-38510

**Current Rating Per Characteristic:**

140.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

85.00 nanoseconds propagation delay time, high to low level output and 40.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Prom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

18 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0