## NSN 5962-01-099-6482

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-099-6482

view Offiline at https://aerobasegroup.com/histi/3302-01-033-0402
Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
2.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, bus buffer
Case Outline Source And Designator:
To-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
15.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Specification Data:
18876-13041727-1 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-099-6482

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0