# NSN 5962-01-100-6050

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-100-6050

## **Body Length:**

Between 0.750 inches and 0.785 inches

## Body Width:

Between 0.240 inches and 0.295 inches

## **Body Height:**

Between 0.160 inches and 0.180 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and low power and negative outputs and positive outputs

#### Inclosure Material:

Ceramic

#### **Inclosure Configuration:**

Dual-in-line

#### Output Logic Form:

Complementary-metal oxide-semiconductor logic

## Input Circuit Pattern:

Hex 1 input

## **Design Function And Quantity:**

6 schmitt trigger

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

18.5 volts power source

## **Time Rating Per Chacteristic:**

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

## Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0