NSN 5962-01-101-2408

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-101-2408

View Online at https://aerobasegroup.com/nsn/5962-01-101-2408
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.292 inches
Body Height:
Between 0.134 inches and 0.204 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/enable and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 decoder, two to four line
Terminal Surface Treatment:
Solder
Product Name:
Decoder/demultiplexer
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
09344-pc73670 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

A458a0

Fiig:

Yes - demil/mli