

View Online at <https://aerobasegroup.com/nsn/5962-01-101-9600>

Overall Length:

0.400 inches

Overall Height:

0.330 inches

Overall Width:

0.310 inches

Body Length:

0.400 inches

Body Width:

0.280 inches

Body Height:

Between 0.145 inches and 0.180 inches

Maximum Power Dissipation Rating:

1050.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 driver, peripheral

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

65.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0