NSN 5962-01-102-6235

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-102-6235

| Body Length: |
|-----------------------------------------------------------------------------------------------------------|
| Between 0.755 inches and 0.785 inches |
| Body Width: |
| Between 0.245 inches and 0.280 inches |
| Body Height: |
| 0.200 inches |
| Maximum Power Dissipation Rating: |
| 198.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| A-10a |
| Features Provided: |
| Low power and schottky |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Criticality Code Justification: |
| Cbbl |
| Design Function And Quantity: |
| 1 shift register, parallel load |
| Product Name: |
| Microcircuit, digital, low power schottky ttl parallel-load 8-bit shift register |
| Voltage Rating And Type Per Characteristic: |
| 4.5 volts power source and 5.5 volts power source and 2.0 volts input logic 1 and 0.7 volts input logic 0 |
| Special Features: |
| Must also withstand a short circuit condition at one outp |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |