## NSN 5962-01-102-7610

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-102-7610 **Body Length:** 1.400 inches **Body Width:** Between 0.514 inches and 0.588 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Teletypewriter set, type an/ugc-129 **Features Provided:** Hermetically sealed and monolithic and positive outputs and asynchronous and programmable and resettable and synchronous and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 19 input

**Design Function And Quantity:** 

1 receiver and 1 transmitter

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

**Time Rating Per Chacteristic:** 

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:** 

19397-st67266 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

28 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

## NSN 5962-01-102-7610

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0