NSN 5962-01-102-7881

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-102-7881

view Online at https://aerobasegroup.com/hsn/5962-01-102-7661
Body Length:
Between 0.750 inches and 0.780 inches
Body Width:
Between 0.245 inches and 0.275 inches
Body Height:
Between 0.120 inches and 0.180 inches
Maximum Power Dissipation Rating:
625.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and high speed and synchronous and presettable and w/open collector
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 counter and 1 counter, universal
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
3.70 nanoseconds propagation delay time, low to high level output and 3.70 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0