## NSN 5962-01-102-9065

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-102-9065

## **Body Length:** 0.390 inches **Body Width:** Between 0.235 inches and 0.260 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 generator, parity, checker **Case Outline Source And Designator:** F-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source **Time Rating Per Chacteristic:** 700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 82577-932876 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a Unit Of Measure:

Demilitarization: Yes - demil/mli

## NSN 5962-01-102-9065

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

