## NSN 5962-01-103-5072

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-103-5072
Body Length:
Between 0.740 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.280 inches
Body Height:
Between 0.110 inches and 0.180 inches
Maximum Power Dissipation Rating:
900.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
8 channel
Design Function And Quantity:
1 multiplexer, analog
Terminal Surface Treatment:
Gold or tin
Voltage Rating And Type Per Characteristic:
-32.0 volts power source and 0.0 volts power source
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
12436-6010396 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5962-01-103-5072

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0