NSN 5962-01-103-8432

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-103-8432 **Body Length:** 0.380 inches **Body Width:** 0.250 inches **Body Height:** 0.130 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/open collector **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 converter, voltage to frequency **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 100.00 nanoseconds agc threshold blank and 100.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0