NSN 5962-01-103-9824



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-103-9824 **Body Length:** 0.280 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.085 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/enable and w/field effect transistor switch **Inclosure Material:** Silicon **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 channel **Design Function And Quantity:** 2 driver, switch, field effect transistor and 2 switch, analog **Case Outline Source And Designator:** F-1 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 22.0 volts power source **Time Rating Per Chacteristic:** 1600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 14933-78014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0