NSN 5962-01-103-9825



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-103-9825 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 825.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/enable and w/field effect transistor switch **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 channel **Design Function And Quantity:** 2 driver, switch, field effect transistor and 2 switch, analog **Case Outline Source And Designator:** D-1 mil-m-38510 **Current Rating Per Characteristic:** 3.00 milliamperes supply **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic:

22.0 volts power source

Time Rating Per Chacteristic:

1600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

14933-78014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-103-9825

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0