## NSN 5962-01-104-5833

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-104-5833

| Body Outside Diameter:  |
|---|
| Between 0.209 inches and 0.230 inches   |
| Body Height:  |
| 0.090 inches  |
| Maximum Power Dissipation Rating:   |
| 100.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and negative outputs and positive outputs  |
| Inclosure Material:   |
| Metal   |
| Inclosure Configuration:  |
| Can   |
| Input Circuit Pattern:  |
| 1 input   |
| Design Function And Quantity:   |
| 1 regulator, voltage  |
| Terminal Surface Treatment:   |
| Gold  |
| Precious Material And Location:   |
| Terminal surface gold   |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 98230-on220754 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                   |
| Terminal Type And Quantity:   |
| 2 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| A458a0  |
|   |