NSN 5962-01-104-7722

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-104-7722 **Body Length:** 0.875 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Dual 3 input **Design Function And Quantity:** 2 decoder, binary to one of four **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 10.00 milliamperes supply **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.0 volts total supply **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 pin **Specification Data:** 81349-mil-m-38510/173 government specification

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-104-7722

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0