

View Online at <https://aerobasegroup.com/nsn/5962-01-104-9096>

Body Length:

Between 0.815 inches and 0.840 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

0.140 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

4910-01-222-6589; vtm/transducer kit, tm 9-4910-571-34&p, 17 feb 89

Features Provided:

Burn in and monolithic

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 3 input

Design Function And Quantity:

1 multivibrator, monostable

Time Rating Per Characteristic:

700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output

Special Features:

Cos/mos dual monostable multivibrator intergrated circuit in a16 lead dual line plastic package. Testjtc19207-12258822

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

1 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0