NSN 5962-01-105-3645



05-3645

| Linear Microcircuit - Page 1 of 1 | |
|--|---|
| View Online at https://aerobasegroup.com/nsn/5962-01-1 | 0 |
| Body Length: | |
| 2.300 inches | |
| Body Width: | |
| 2.300 inches | |
| Body Height: | |
| 0.400 inches | |
| Operating Tempurature Range: | |
| -0.0/+70.0 degrees celsius | |
| Storage Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Features Provided: | |
| High speed and dc coupled and schottky | |
| Inclosure Material: | |
| Plastic | |
| Inclosure Configuration: | |
| Dual-in-line | |
| Input Circuit Pattern: | |
| 2 input | |
| Design Function And Quantity: | |
| 1 amplifier, operational, general purpose | |
| Terminal Surface Treatment: | |
| Gold | |
| Product Name: | |
| Amplifier, sample/track-and-hold single | |
| Voltage Rating And Type Per Characteristic: | |
| 2.0 volts power source | |
| Precious Material And Location: | |
| Terminal surface gold | |
| Precious Material: | |
| Gold | |
| Terminal Type And Quantity: | |
| 22 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |
| | |