

View Online at <https://aerobasegroup.com/nsn/5962-01-105-3656>

Body Length:

0.870 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

195.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and w/storage and w/enable and synchronous

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

4 multiplexer

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

27.00 nanoseconds propagation delay time, low to high level output and 32.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96214-537880 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0