## NSN 5962-01-105-4766

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-105-4766 **Body Length:** Between 0.710 inches and 0.770 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 10.0 milliwatts **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bipolar and monolithic and positive outputs and w/schmitt trigger and w/totem pole output **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nand **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 22.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0