NSN 5962-01-105-5551

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-105-5551 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 670.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator, voltage, differential **Case Outline Source And Designator:** T0-116 joint electron device engineering council **Terminal Surface Treatment:**

Solder

Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 8.0 volts power source

Time Rating Per Chacteristic:

30.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0