NSN 5962-01-108-4742

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-108-4742

view Online at https://aerobasegroup.com/nsn/5962-01-108-4742
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
1260.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs and internally compensated
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 amplifier, operational, general purpose
Case Outline Source And Designator:
To-116 joint electron device engineering council
Current Rating Per Characteristic:
50.00 milliamperes reverse current, dc microamperes
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
32.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0