NSN 5962-01-109-3299

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-109-3299 |
|--|
| Body Length: |
| Between 0.880 inches and 0.900 inches |
| Body Width: |
| Between 0.485 inches and 0.495 inches |
| Maximum Power Dissipation Rating: |
| 1.5 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, general purpose and 1 buffer |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 40.0 volts power source |
| Time Rating Per Chacteristic: |
| 1.50 nanoseconds propagation delay time, low to high level output |
| Terminal Type And Quantity: |
| 8 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0