## NSN 5962-01-109-4228

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-109-4228

| Body Length:   |
|--|
| 0.840 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches  |
| Body Height:   |
| Between 0.140 inches and 0.185 inches  |
| Maximum Power Dissipation Rating:  |
| 479.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and schottky and 3-state output   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| Quad 2 input and 1 input and 1 input   |
| Design Function And Quantity:  |
| 4 selector, data and 4 multiplexer   |
| Case Outline Source And Designator:  |
| D-2 mil-m-38510  |
| Current Rating Per Characteristic:   |
| 87.00 milliamperes output  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 5.5 volts power source   |
| Special Features:  |
| Inputs are data, quad-2, data select 1 and output enable   |
| Test Data Document:  |
| 14933-80023 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                            |
| Terminal Type And Quantity:  |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## NSN 5962-01-109-4228

Digital Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

