NSN 5962-01-110-1575

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-110-1575

Overall Height:
0.380 inches
Body Length:
Between 0.753 inches and 0.785 inches
Body Width:
Between 0.265 inches and 0.285 inches
Body Height:
Between 0.140 inches and 0.170 inches
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and w/resistor and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
Design Function And Quantity: 4 amplifier, operational, general purpose
-
4 amplifier, operational, general purpose
4 amplifier, operational, general purpose Current Rating Per Characteristic:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit Shelf Life:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:
4 amplifier, operational, general purpose Current Rating Per Characteristic: 7.00 milliamperes reverse current, dc absolute Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts input Time Rating Per Chacteristic: 140.00 nanoseconds rise transient Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: