## NSN 5962-01-110-1616



Digital-linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-110-1616 **Body Length:** 0.785 inches **Body Width:** 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/inhibit and bidirectional and positive outputs and dynamic **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 4 input and 8 channel **Design Function And Quantity:** 1 multiplexer/demultiplexer, analog **Case Outline Source And Designator:** Mo-001ac joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 720.00 nanoseconds propagation delay time, low to high level output and 720.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Fiig: A458a0

No

**Demilitarization:**