NSN 5962-01-110-3479



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-110-3479 **Body Length:** 1.425 inches **Body Width:** 0.600 inches **Body Height:** 0.120 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 16 channel **Design Function And Quantity:** 1 multiplexer, analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -17.0 volts power source and 17.0 volts power source **Time Rating Per Chacteristic:** 8000.00 nanoseconds propagation delay time, low to high level output and 8000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 12436-6010426 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli