## NSN 5962-01-110-7285

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-110-7285

Body Length:
1.000 inches
Body Width:
0.750 inches
Body Height:
0.500 inches
Operating Tempurature Range:
-0.0/+60.0 degrees celsius
Storage Tempurature Range:
-65.0/+100.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
1 input
Design Function And Quantity:
Design Function And Quantity: 1 oscillator, crystal controlled
•
1 oscillator, crystal controlled
1 oscillator, crystal controlled  Terminal Surface Treatment:
1 oscillator, crystal controlled  Terminal Surface Treatment:  Solder
1 oscillator, crystal controlled  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:
1 oscillator, crystal controlled  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.0 volts power source
1 oscillator, crystal controlled  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  5.0 volts power source  Terminal Type And Quantity:
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life:
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life: N/a
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life: N/a
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life: N/a  Unit Of Measure:
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
1 oscillator, crystal controlled  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 5.0 volts power source  Terminal Type And Quantity: 6 printed circuit  Shelf Life: N/a  Unit Of Measure: Demilitarization: Yes - demil/mli