# NSN 5962-01-111-0893

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-111-0893

## **Body Length:** 1.425 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.165 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable and w/decoded output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:**

16 channel

**Design Function And Quantity:** 

2 multiplexer, analog

**Terminal Surface Treatment:** 

Solder

#### Voltage Rating And Type Per Characteristic:

33.0 volts power source

#### **Time Rating Per Chacteristic:**

125.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

07187-4045387 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Terminal Type And Quantity:**

28 printed circuit

Shelf Life:

N/a

### Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0