NSN 5962-01-111-7859

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-111-7859

Bodv	l er	nath:
Dogv		IMUI.

Between 1.235 inches and 1.290 inches

Body Width:

Between 0.515 inches and 0.560 inches

Body Height:

Between 0.130 inches and 0.155 inches

Operating Tempurature Range:

-40.0/+85.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and bipolar and resettable and synchronous and unipolar and w/enable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Design Function And Quantity:

1 encoder and 1 decoder

Terminal Surface Treatment:

Solder

Product Name:

Manchester encoder-decoder single

Voltage Rating And Type Per Characteristic:

7.3 volts power source

Time Rating Per Chacteristic:

110.00 nanoseconds propagation delay time, low to high level output and 110.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

70210-513-180 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0