NSN 5962-01-111-9745

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-111-9745

| Body Outside Diameter: |
|---|
| Between 0.209 inches and 0.219 inches |
| Body Height: |
| Between 0.075 inches and 0.093 inches |
| Maximum Power Dissipation Rating: |
| 250.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Training set, tactical electronic warfare, type an/mst-ti |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 regulator, voltage |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| 3.9 volts power source |
| Precious Material And Location: |
| Terminal surface gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Terminal Type And Quantity: |
| 2 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0