

View Online at <https://aerobasegroup.com/nsn/5962-01-112-1022>

**Maximum Power Dissipation Rating:**

76.0 milliwatts

**Operating Temperature Range:**

-0.0/+80.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and high speed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 4 input

**Design Function And Quantity:**

2 gate, nand

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

05869-717129-520 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0